

10/597482

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)


PCT

(10) International Publication Number
WO 2005/086405 A3

- (51) International Patent Classification⁷: H04L 1/00
- (21) International Application Number: PCT/US2005/006842
- (22) International Filing Date: 3 March 2005 (03.03.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/549,804 3 March 2004 (03.03.2004) US
60/555,982 24 March 2004 (24.03.2004) US
- (71) Applicant (for all designated States except US): AWARE, INC. [US/US]; 40 Middlesex Turnpike, Bedford, MA 01730 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): TZANNES, Marcos, C. [US/US]; 121 La Espiral, Orinda, CA 94563 (US).
- (74) Agents: VICK, Jason, H. et al.; Miles & Stockbridge P.C., 1751 Pinnacle Dr., Suite 500, McLean, VA 22102-3833 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: IMPULSE NOISE MANAGEMENT



(57) Abstract: Evaluation of the impact of impulse noise on a communication system can be utilized to determine how the system should be configured to adapt to impulse noise events. Moreover, the system allows for information regarding impulse noise events, such as length of the event, repetition period of the event and timing of the event, to be collected and forwarded to a destination. The adaptation can be performed during one or more of Showtime and initialization, and can be initiated and determined at either one or more of a transmitter and a receiver.

WO 2005/086405 A3



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:

1 December 2005